

DECLARATION OF PERFORMANCE

CP250 FLEX CAM

 Unique identification code of the product-type: CP250 FLEX CAM

- 2. Intended use of the construction product: Improved cementitious adhesive for internal and external tiling on floors and walls
- 3. Manifacturer:

EDMEC branded products are manifactured and distributed by:

D.M. S.r.l. unipersonale
Via Scala n°628/D
41038 San Felice s/P (MO)
Part. Iva e Cod. Fisc.: 03728460365

info@edmec.it

4. System of AVCP: System 4

5. Harmonized standard: EN 12004:2007+A1:2012

6. Declared performance:

<u>Descrizione</u>	<u>Dati</u>
Reaction to fire	Class A2 _{FL} -s1 / A2-s1, d0
Initial tensile adhesion strength	≥ 1.00 N/mm²
Tensile adhesion strength after heat	≥ 1.00 N/mm²
Tensile adhesion strength after water immersion	≥ 1.00 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1.00 N/mm²
Release of dangerous substances	See SDS

The technical data sheet given here is based on our technical and practical knowledge.

D.M. SRLS UNIPERSONALE is not responsible for injury, loss or damage arasing from the improper use of the above informations.

Please note that additions and/or amendments to this information may be made over time by D.M. SRLS UNIPERSONALE without notice.

Technical documentation: not applicable

The performance of the product identified above is in conformoty with the set of declared performance.

This declaration of performance is issued, in accoradnce with Regulation (EU) n. 305/2011 and 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on beahalf of the manufacturer